





TYPICAL WIRING DIAGRAM


## NOTES:

1. ALL UNITS ARE cUL LISTED AND DESIGNED ACCORDANCE WITH INDUSTRY STANDARDS.
2. TRANSFORMERS ARE DRY-TYPE, CLASS AA, VENTILATED NEMA 2 ENCLOSED FOR INDOOR USE.
3. TRANSFORMERS ARE FLOOR MOUNTED.
4. AVAILABLE ACCESSORIES FOR THIS UNIT:  
A) OUTDOOR WEATHERSHIELD KIT  
B) WALL MOUNTING BRACKETS
5. TRANSFORMERS ARE CONSTRUCTED BASED UPON A 40°C AMBIENT ENVIRONMENT.
6. MAINTAIN 1" CLEARANCE FROM ALL LIVE PARTS.
7. PAINT COLOR IS ANSI #61.



FRONT VIEW

SIDE VIEW



TERMINAL DETAILS

## APPROXIMATE DIMENSIONS ( INCHES )

| KVA   | A     | B     | C     | D     | E     | F    | G    | H    | J    | K     | L    | BOX      | lbs. | WEATHER SHIELD | TERMINAL TYPE |
|-------|-------|-------|-------|-------|-------|------|------|------|------|-------|------|----------|------|----------------|---------------|
| 225.0 | 51.00 | 42.12 | 26.00 | 40.25 | 22.75 | ---- | ---- | ---- | ---- | 31.50 | ---- | 3PT-225K | 1320 | WS-12A         | BUSBAR        |

\* ELECTROSTATIC SHIELD GROUNDED TO TRANSFORMER CASE AT FACTORY ( IF APPLICABLE )

DRAWINGS  
☒ APPROVAL  
☐ RECORD  
☐ OTHER

|                        |                                                                              |                                                              |            |
|------------------------|------------------------------------------------------------------------------|--------------------------------------------------------------|------------|
| PRIMARY VOLTAGE        | 208-240 DELTA                                                                | CUST.                                                        | XXXXXXXXXX |
| SECONDARY VOLTAGE      | 208Y/120                                                                     | JOB                                                          |            |
| TEMPERATURE RISE IN °C | 150                                                                          | CATALOG                                                      |            |
| WINDINGS & TERMINALS   | <input checked="" type="checkbox"/> ALUMINUM <input type="checkbox"/> COPPER | NOTE                                                         | XXXXXXX    |
| FREQUENCY IN HERTZ     | 60                                                                           | BY                                                           | ENG. LOG.  |
| PRIMARY TAPS           | 201, 214, 222, 228, 234, 247, 254                                            | DATE                                                         | TITLE      |
|                        |                                                                              | REV                                                          | MFG. LOG.  |
|                        |                                                                              | DATE:                                                        | DWG. FILE  |
|                        |                                                                              | DWG. NO.                                                     |            |
|                        |                                                                              | 3-PHASE, 600 VOLT CLASS<br>ISOLATION<br>DRY TYPE TRANSFORMER |            |
|                        |                                                                              | 3PTN043-225K-240                                             |            |

POWERTRAN