



1. ALL UNITS ARE CUL LISTED & DESIGNED ACCORDANCE WITH INDUSTRY STANDARDS.
2. TRANSFORMERS ARE DRY-TYPE, CLASS AA, VENTILATED, OPEN-STYLE ASSEMBLY FOR INDOOR/CONTROL PANEL USE.
3. TRANSFORMER ARE BASE MOUNTED.
4. TRANSFORMERS ARE CONSTRUCTED BASED UPON A 40°C AMBIENT ENVIRONMENT.
5. MAINTAIN 1" CLEARANCE FROM ALL LIVE PARTS.



| KVA   | A    | B    | C    | D    | E    | 3-POLE PRIMARY<br>FUSE BLOCK | PRIMARY<br>COVER | SECONDARY<br>COVER | HARDWARE | (4) MTG SLOTS   | STEEL  | STACK | WEIGHT |
|-------|------|------|------|------|------|------------------------------|------------------|--------------------|----------|-----------------|--------|-------|--------|
| 0.250 | 4.50 | 5.25 | 5.75 | 2.50 | 2.50 | INCLUDED                     | INCLUDED         | INCLUDED           | 1/4-20   | 0.250" x 0.562" | EI-175 | 1.50  | 15     |

|                                                                                    |                                                                              |                  |           |                                                                     |
|------------------------------------------------------------------------------------|------------------------------------------------------------------------------|------------------|-----------|---------------------------------------------------------------------|
| PRIMARY VOLTAGE                                                                    | 200-208-230-240-277-380-400<br>415-440-460-480-550-575-600                   | CUST.            |           | XXXXXXXX                                                            |
| SECONDARY VOLTAGE                                                                  | 120                                                                          | JOB              |           |                                                                     |
| TEMPERATURE RISE IN °C                                                             | 55                                                                           | CATALOG          |           |                                                                     |
| WINDINGS & TERMINALS                                                               | <input type="checkbox"/> ALUMINUM <input checked="" type="checkbox"/> COPPER | NOTE<br>XXXXXXXX |           |                                                                     |
| FREQUENCY HERTZ                                                                    | 50/60                                                                        | BY               | ENG. LOG. | TITLE<br>1-PHASE, 600 VOLT CLASS<br>CONTROL<br>DRY TYPE TRANSFORMER |
| PRIMARY TAPS                                                                       | NONE                                                                         | DATE             |           |                                                                     |
|  |                                                                              | REV              | MFG. LOG. | DWG. NO.<br><br>A965MT250-3FB                                       |
|                                                                                    |                                                                              | DATE:            | DWG. FILE |                                                                     |