



1. ALL UNITS ARE cUL LISTED & DESIGNED ACCORDANCE WITH INDUSTRY STANDARDS.
2. TRANSFORMERS ARE DRY-TYPE, CLASS AA, ENCAPSULATED NEMA 12 ENCLOSED FOR INDOOR / DUSTPROOF USE.
3. TRANSFORMERS ARE WALL / MACHINE MOUNTABLE VIA THE ATTACHED BRACKETS.
4. TRANSFORMERS ARE CONSTRUCTED BASED UPON A 40°C AMBIENT ENVIRONMENT.
5. MAINTAIN 1" CLEARANCE FROM ALL LIVE PARTS.
6. PAINT COLOR IS RAL# 7042.



APPROXIMATE DIMENSIONS ( INCHES )

| KVA  | A     | B     | C    | D    | E     | F     | HARDWARE | MTG SLOTS       | ENCLOSURE | lbs. | WEATHER SHIELD | TERMINAL TYPE |
|------|-------|-------|------|------|-------|-------|----------|-----------------|-----------|------|----------------|---------------|
| 10.0 | 15.25 | 12.38 | 9.00 | 8.50 | 11.25 | ----- | 3/8-16   | 0.437" x 0.750" | N10       | 145  | N/A            | LEADs         |

\* ELECTROSTATIC SHIELD GROUNDED TO TRANSFORMER CASE AT FACTORY ( IF APPLICABLE )

DRAWINGS  
☒ APPROVAL  
☐ RECORD  
☐ OTHER

|                                                                                    |                                                                              |                                           |           |                                                                    |
|------------------------------------------------------------------------------------|------------------------------------------------------------------------------|-------------------------------------------|-----------|--------------------------------------------------------------------|
| PRIMARY VOLTAGE                                                                    | 208-240                                                                      | CUST. XXXXXXXXX                           |           |                                                                    |
| SECONDARY VOLTAGE                                                                  | 230                                                                          | JOB                                       |           |                                                                    |
| TEMPERATURE RISE IN °C                                                             | 115                                                                          | CATALOG                                   |           |                                                                    |
| WINDINGS & TERMINALS                                                               | <input type="checkbox"/> ALUMINUM <input checked="" type="checkbox"/> COPPER | NOTE IMPORTED MACHINERY ( HOT, NEU, GRD ) |           |                                                                    |
| FREQUENCY IN HERTZ                                                                 | 60                                                                           | BY                                        | ENG. LOG. | TITLE 1-PHASE, 600 VOLT CLASS<br>ISOLATION<br>DRY TYPE TRANSFORMER |
| PRIMARY TAPS                                                                       | NONE                                                                         | DATE                                      |           |                                                                    |
|  |                                                                              | REV                                       | MFG. LOG. | DWG. NO.<br><br>NF905L10                                           |
|                                                                                    |                                                                              | DATE:                                     | DWG. FILE |                                                                    |