



1. ALL UNITS ARE cUL LISTED AND DESIGNED ACCORDANCE WITH INDUSTRY STANDARDS.
2. TRANSFORMERS ARE DRY-TYPE, CLASS AA, VENTILATED NEMA 2 ENCLOSED FOR INDOOR USE.
3. TRANSFORMERS ARE FLOOR MOUNTED.
4. AVAILABLE ACCESSORIES FOR THIS UNIT:
 - A) OUTDOOR WEATHERSHIELD KIT
 - B) WALL MOUNTING BRACKETS
5. TRANSFORMERS ARE CONSTRUCTED BASED UPON A 40°C AMBIENT ENVIRONMENT.
6. MAINTAIN 1" CLEARANCE FROM ALL LIVE PARTS.
7. PAINT COLOR IS ANSI# 61.



KVA	A	B	C	D	E	F	G	H	J	K	BOX	WEIGHT	WEATHER SHIELD	TERMINAL TYPE
25.0*	33.00	16.63	18.38	15.00	15.00	4.00	4.00	1.00	5.75	22.50	PT-15K	260	WS-3	BUSBAR

DRAWINGS
☒ APPROVAL
☐ RECORD
☐ OTHER

PRIMARY VOLTAGE	240 x 480		CUST. XXXXXXXXXXXX		
SECONDARY VOLTAGE	120 x 240		JOB		
TEMPERATURE RISE IN °C	150		CATALOG		
WINDINGS & TERMINALS	☐ ALUMINUM	☒ COPPER	NOTE ELECTROSTATICALLY SHIELDED		
FREQUENCY IN HERTZ	60		BY	ENG. LOG.	TITLE 1-PHASE, 600 VOLT CLASS ISOLATION DRY TYPE TRANSFORMER
PRIMARY TAPS	216, 228, 252 432, 444, 456, 468, 492, 504		DATE		
			REV	MFG. LOG.	DWG. NO. PT104-25K-CU-EE
			DATE:	DWG. FILE	